

MODEL YEAR 2023 | CVO™ ROAD GLIDE® LTD ANNIVERSARY

Dimensions	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Length	101.2 in. (2,570 mm)	
Overall Width	43.1 in. (1,095 mm)	
Overall Height	56.5 in. (1,435 mm)	
Seat Height, Laden	28.2 in. (716 mm)	
Seat Height, Unladen	29.9 in. (760 mm)	
Static Ground Clearance	5.1 in. (130 mm)	
Rake (steering head) (deg)	26	
Fork Angle (deg)	29.25	
Trail	6.7 in. (170 mm)	
Wheelbase	64 in. (1,625 mm)	
Tires, Type	Dunlop® Harley-Davidson Series, bias blackwall front and rear	
Tires, Front Model	D408F	
Tires, Front Specification	BW 130/60B19 61H	
Tires, Rear Model	D407	
Tires, Rear Specification	BW 180/55B18 80H	
Fuel Capacity	6 gal. (22.7 l)	
Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)	
Oil Capacity (w/filter)	5 qt. (4.7 l)	
Transmission Capacity	1 qt. (.95 l)	
Primary Chain Case Capacity	1.1 qts. (1 l)	
Coolant Capacity	0.8 qt. (0.75 l)	
Weight, As Shipped	927 lb. (420 kg)	
Weight, In Running Order	963 lb. (437 kg)	
Gross Vehicle Weight Rating	1,360 lb. (617 kg)	
Gross Axle Weight Rating, Front	500 lb. (227 kg)	
Gross Axle Weight Rating, Rear	927 lb. (420 kg)	

Luggage Capacity -Volume

4.7 cu ft (0.132 m3)

Engine	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Engine	Twin-Cooled™ Milwaukee-Eight® 117	
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder	
Bore	4.075 in. (103.5 mm)	
Stroke	4.5 in. (114.3 mm)	
Displacement	117 cu in (1,923 cc)	
Compression Ratio	10.2:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	
Air Cleaner	Paper, washable	
Exhaust	Dual, with crossover	
Lubrication System	Pressurized, dry-sump	

Drivetrain	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Primary Drive	Chain, 34/46 ratio	
Final Drive	Belt, 32/68 ratio	
Clutch	Mechanically actuated 10 plate, wet Assist & Slip	
Transmission	6-Speed Cruise Drive®	
Gear Ratios	9.593	
Gear Ratios	6.65	
Gear Ratios	4.938	
Gear Ratios	4	
Gear Ratios	3.407	
Gear Ratios	2.875	

Chassis	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Frame	Mild steel; tubular frame; two-piece stamped	

	and welded backbone; cast and forged junctions; twin downtubes; bolt-on rear frame with forged fender supports; MIG welded.	
Swingarm	Mild steel; two-piece drawn and welded section; forged junctions; MIG welded.	
Front Fork	49mm Dual Bending Valve	
Rear Shocks	Premium standard height hand-adjustable rear suspension	
Wheels, Optional Style Type	N/A	
Wheels, Front Type	Gloss Black and Contrast Chrome Tomahawk	
Wheels, Front Width	3 in. (76 mm)	
Wheels, Front Height	19 in. (483 mm)	
Wheels, Rear Type	Gloss Black and Contrast Chrome Tomahawk	
Wheels, Rear Width	5 in. (127 mm)	
Wheels, Rear Height	18 in. (457 mm)	
Brakes, Caliper Type	32 mm, 4-piston fixed front and rear	
Brakes, Rotor Type	Dual floating rotors (front), fixed rotor (rear)	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.2 in. (5 mm)	
Brakes, Front is dual	Yes	
Brakes, Rear Diameter	11.8 in. (300 mm)	
Brakes, Rear Thickness	0.28 in. (7.1 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.6 in. (117 mm)	
Suspension Travel, Rear	3 in. (76 mm)	

Performance	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Engine Torque Testing Method	J1349	
Engine Torque	125 ft-lb (169 Nm)	
Engine Torque	3,500	
Power	102 HP / 76 kW @ 4750 rpm	
Lean Angle Testing Method	J1168	
Lean Angle, Right (deg.)	34.3	
Lean Angle, Left (deg.)	33.4	
Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	41 mpg (5.7 l/100 km)	

CO ² Emissions Testing Method	N/A	
CO ² Emissions	N/A	

Electric	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Battery	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca (per Battery Council International Rating)	
Charging	Three-phase, 48-amp system (600W @13V, 2000 RPM, 625W max power @ 13V)	
Starting	1.6 kW electric with solenoid shift starter motor engagement	
Lights (as per country regulation), Headlamp	LED 34-watt, 915 lumen low beam, 37-watt, 915 lumen high beam.	
Lights (as per country regulation), Tail/Stop	LED	
Lights (as per country regulation), Front Signal Lights	LED	
Lights, Rear Turn Signals	LED	
Gauges	- Custom gauges styled to complement each CVO vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	
Auxiliary Lamps	N/A	
Electric Power Outlet	Electric power accessory port in fairing and tourpak	
GPS System	Boom!™ Box GTS audio system with GPS and touchscreen	
Reverse Gear	N/A	

Warranty And Service	FLTRKSEANV CVO™ Road Glide® LTD Anniversary	Notes
Warranty	24 months (unlimited mileage)	
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter	

